

901. UNDERWAY CHECK LIST

- _____ STOW COMPANIONWAY BOARD
- _____ CHECK BILGE LEVEL
- _____ PREP NAV ITEMS, INCLUDING: (SEE SECTION 208.3)
 - CHARTS (12270,12282,12283 FOR LOCAL OPS)
 - HAND BEARING COMPASS
 - NAV KIT
 - OFFSHORE YACHT LOG
 - BEARING LOG
 - NAVIGATION WORKBOOK
 - PUBS
- _____ VERIFY REQUIRED SAFETY EQUIPMENT, INCLUDING:
 - PFDS (ONE FOR EACH PERSON)
 - BOAT HOOK
 - TWO ANCHORS WITH RODES ATTACHED
 - HORN & BELL
 - MOB POLE/LIFE RING WITH STROBE/LIFE SLING WITH STROBE/THROW SOCK
 - 3 DRY CHEM FIRE EXTINGUISHERS (GALLEY, LINE LOCKER, PORT CLOSET)
 - 1 CO2 FIRE EXTINGUISHER AFT OF NAV DESK
- _____ PLACE ENSIGN ON STAFF ON STERN PULPIT
- _____ REMOVE HELM AND MAINSAIL COVERS
- _____ BREAKDOWN THE INNER FORESTAY LEADING IT AROUND THE FAIRLEAD ON THE PORT SIDE OF THE MAST SECURING IT TO THE BUNGEE CORD ON THE CABIN TOP BENEATH THE BOOM VANG
- _____ MOVE JIB & SPINNAKER HALYARDS AND TOPPING LIFT BACK TO THE BASE OF THE MAST
- _____ VERIFY NAVIGATION LIGHT OPERATION IF YOU ARE GOING TO BE OUT AFTER SUNSET OR IN REDUCED VISIBILITY
- _____ SECURE A/C BATTERY CHARGER
- _____ SECURE A/C MAIN CIRCUIT BREAKER
- _____ DISCONNECT SHORE POWER (PIER, THEN BOAT)

DNASINST 3120.1D

- _____ STOW SHORE POWER CABLE (PORT LOCKER) OR COIL ON PIER
- _____ ENERGIZE D/C MAIN CIRCUIT BREAKER
- _____ TURN ON BOTH ALTERNATOR CIRCUIT BREAKERS
- _____ SELECT THE SHIP SERVICE PERKO SWITCH TO BOTH
- _____ CONDUCT ENGINE START CHECKS IAW ENGINE START CHECKLIST 902
- _____ RUN REEFING LINES. ENSURE LINES FREE TO RUN
- _____ PRESET HYDRAULIC BACKSTAY TO 2000 PSI
- _____ ENERGIZE THE FOLLOWING EQUIPMENT:
 - VHF RADIO (SET TO SCAN 09, 12, 13, 16 & 82A)
 - LORAN/GPS
 - SAILING INSTRUMENTS (AND DEPTH SOUNDER FOR NA1-NA8)
- _____ LISTEN TO VHF WEAX BROADCAST
- _____ CONDUCT NAVIGATION/SAFETY BRIEF
- _____ MAKE LINE HANDLING ASSIGNMENTS
- _____ FAKE SPRING LINES ON THE FRIENDSHIP LINES
- _____ OBTAIN PERMISSION TO GET UNDERWAY
- _____ GET UNDERWAY

NOTE

RESELECT SCAN AFTER OBTAINING PERMISSION TO UNDERWAY